



Freightliner M2 Straight Truck

INCREASE CUSTOMER SATISFACTION WITH A
TRUCK YOU CAN TRUST MILE AFTER MILE

Ryder commercial trucks offer big help for any load. They're loaded with features to make driving, loading, and unloading easier. And you can choose from a range of body sizes and vehicle weights with features like automatic transmissions, power steering, A/C, hydraulic lift gates, ramps and slat interiors. Nobody helps you tackle big loads like Ryder.



FREIGHTLINER M2

Ryder has the right vehicle for your company and for your bottom line. To learn more contact us at **1-800-RYDER-OK Ext. 1808 (1-800-793-3765)** or visit us at today **www.ryder.com**

FREIGHTLINER M2

**CHASSIS AND CAB**

- ▶ Model M2 106md SA (4x2)
- ▶ GVWR 33,000#
- ▶ BBC 106.0" C/L - F/A 40.7"
- ▶ WB 270"
- ▶ CA 204"
- ▶ CF 282" af 78"
- ▶ Body length 312" (28')

AXLE, FRONT

- ▶ Meritor mfs-12-143a 12,000#

AXLE, REAR

- ▶ Meritor rs-21-145 21,000#
- ▶ Gear ratio 4.11 (65 MPH)

BRAKES, SERVICE

- ▶ Wabco ABS brake system
- ▶ Air brake system
- ▶ BW AD-IP air dryer w/htr
- ▶ Meritor SLK adj unhand, frt/rr

CAB

- ▶ Conventional cab, 106" BBC
- ▶ 8" LH/RH convex ss mirrors
- ▶ Electronic W/S wiper w/delay
- ▶ Base vinyl interior
- ▶ Color - opal gray vinyl
- ▶ 102" wide mirror brackets
- ▶ Bostrom 910 hi-bk, air lh
- ▶ (2)man pass seat w/tool box
- ▶ F/L xta-2100 am/fm/wb cass.
- ▶ Htr/defroster w/air-cond

ENGINE

- ▶ C7 EP04 210hp @ 2200 RPM
- ▶ 605# ft torque @ 1440 RPM
- ▶ RSG GOV set @ 65 MPH
- ▶ Cruise control set @ 65 MPH

EXHAUST

- ▶ RH horiz muffler & tailpipe

FRAME

- ▶ FRM:11/32"x3-1/2"x10-15/16"
- ▶ 78" rear frame overhang

FUEL TANKS

- ▶ 50 gal aluminum lh tank
- ▶ 50 gal aluminum rh tank

PAINT

- ▶ Imron 5000 N0006H white
- ▶ Chassis - black
- ▶ Bumper paint: argent silver
- ▶ (2) powdercoat frt whls wht
- ▶ (4) powdercoat rr whls wht.

STEERING

- ▶ TRW THP-60 power steering
- ▶ 18" steering wheel

SUSPENSION

- ▶ Frt spgs: 12,000# taperleaf
- ▶ Rear springs: 23,000# cap

TIRES

- ▶ Bridgestone, low profile
- ▶ (2) 295/75R22.5 R260F
- ▶ (4) 295/75R 22.5 14P M726EL

TRANSMISSION

- ▶ fuller fs6406a, 6-spd trans

WHEELS AND RIMS

- ▶ 10-hub piloted wheels
- ▶ (2) 22.5x8.25 accu #28487
- ▶ (4) 22.5x8.25 accu #28487

Body**BASE SPECIFICATIONS**

- ▶ Model GVSD97-26
- ▶ Length: inside 25' 11-1/4"
outside 26' 5-5/8"
- ▶ Height: inside 97-1/8"
outside 103-3/8"
- ▶ Width: inside 98-3/8"
outside 102"

CROSSMEMBERS

- ▶ I-Beam crossmembers

FLOOR

- ▶ 1-3/8" laminated hardwood

BUMPER, D.O.T

- ▶ 10" Wood-filled bumper

DOOR, REAR

- ▶ Whiting alum covered/rollup
- ▶ Rear door opening width 94"

ROOF

- ▶ .032" one-piece aluminum

INTERIOR LINING

- ▶ Front: 4 rows apitong slats
3/4" x 10-1/2" apitong scuff
- ▶ Side: 5 rows apitong slats
3/4" x 10-1/2" apitong scuff

DOME LIGHTS RED

- ▶ (2) Recessed with switch and telltale light in cab

GRABHANDLE

- ▶ (1) curbside
- ▶ (1) roadside each mounted on rear corner posts mounted on sides.
- ▶ (2) rows "e" track surface mounted on sides located 36" & 66" floor to centerline

BODY OPTIONS

- ▶ 26' body pkg
- ▶ Air suspension
- ▶ Dual exterior grabhandles
- ▶ Tilt / telescopic steering column
- ▶ Curbside door
- ▶ 24'
- ▶ 91" height
- ▶ 103" height
- ▶ 26'
- ▶ 91" height
- ▶ 97" height
- ▶ 103" height
- ▶ Walco e-30, 3000 lift gate
- ▶ 72" x 32" platform
- ▶ Walco lift gate ramp combo including 14' walk ramp
- ▶ Power down Walco
- ▶ Whiting plastic covered roll up door